



*CORNIX
STORAGE SYSTEMS
FOR LIFE!*

Cornix Plus

Cornix is manufacturer of storage systems since 1958

CORNIX PLUS® • SHELVING SYSTEM

Unlimited possibilities with the Cornix Plus® evolving boltless system : archive storage, cardboard or plastic bins storage, mezzanines, multi-tier installations (2 to 4 tier), suspended files, garment storage, mobile shelving, etc.

**BEST
SELLER**

**EVOLVING
BOLTLESS SYSTEM**

**1001
applications**

multi-tier installation
(2 tier) for storage of
small parts

multi-tier installation
for suspended files

Cornix Plus® +
Corbox

built-in staircase

SENDZIMIR SHELVES
ALSO AVAILABLE !

an extensive range of
accessories

Cornix Plus® +
Modulbox

Cornix Plus® mobile

Cornix Plus® industrial counters

multi-tier installation 2 tier
+ mezzanine on level 3

**Do you have a specific storage problem ? Cornix Plus® offers you the solution !
Ask for the visit of one of our project engineers !**



Cornix Plus® installation 1 tier + mezzanine on top (surface 2500 m²) intended for a later extension to a multi-tier installation (2 tier + mezzanine on top).



a few years later ...



An original patented CORNIX® shelving system featuring DESIGN & ACCESSORIES and a COST SAVING conception and installation.
Loads up to 400 kg per Cornix Plus® shelf.

The Cornix Plus® shelving system is composed on one hand of uprights & brackets that clic into each other thus creating a solid frame and on the other hand the easily moved shelves.

The upright, a T profile, has a flush unslotted front as to make it more esthetical.
 Standard heights are 1 • 1,75 • 2 • 2,25 • 2,50 • 2,75 • 3 and 3,25 meter. Higher uprights can be obtained by the use of upright sleeves (e.g. for multi-tier installations: 2, 3 ... tier).

The slots on the inside of the upright allow to adjust the position of the shelves per 25 mm. The same slots can also be used to install the full range of accessories.

Each shelf is supported by two brackets that just clic into the upright without the use of tools. The shelf loads depend on the number of shelf stiffeners that are welded to the shelf.

Obviously the Cornix Plus® system can also be combined with the CORBAC range (plastic bins) aswell as with the CORNIX box files.

Cornix Plus® offers you the perfect solution for an adequate storage of small parts, suspended files, archives, garment storage, bulky parts on a mezzanine, etc.

- Cornix Plus® : shelf width 1000 & 1250 mm (height 30 mm)
shelf depth 300 to 800 mm
- Minirack Plus® : shelf width 1200 to 2400 mm (height : 50-70 mm)
shelf depth 400 to 1000 mm and more ...

Briefly Cornix Plus® saves you money and space !

Delivered unassembled. Easy installation.
On request our specialized installers will install your Cornix Plus® shelving system and it's accessories.
Ask for a free quote !





COMPONENTS & ACCESSORIES

Our project engineers are at your disposal for all your questions regarding loads and complex installations. Below an outline of our standard Cornix Plus® racks composed of : 4 T upright (2000 mm high) each time with a plastic base and a plastic top cap; 5 shelves with their brackets; for the starter unit 1 cross bracing is included. For the extension units the cross bracing has to be added when required (1 cross bracing required for every 3 units).

An evolving system as the Cornix Plus® system carries of course a lot of accessories. Below you can find an outline of the main components. This is of course not a limited list. If you don't find that particular accessory that you need, please do not hesitate to consult us so we can look for the best solution to your problem.

- 8. Plinth
- 13. Frame for suspended files
- 14. Reinforcement beams
- 16. Shelfender
- 18. Divider

- 1. T upright.** For the starter unit 4 uprights, 2 for the extension unit. Standard heights : 1 - 1,75 - 2 - 2,25 - 2,50 - 2,75 - 3 - 3,25 meter. Higher uprights can be obtained using the upright sleeves. Standard finish of the uprights : blue RAL 5010.
- 2. Plastic base.** Prevents damage by the upright to your floor or carpet. Two per upright : 1 as base and 1 as finishing cap at the upper side of the upright as to make an esthetical finish. For heavier loads (e.g. mezzanines & multi-tier installations) special steel bases are available.
- 3. Brackets.** Two per shelf. Depths : 300 - 350 - 400 - 500 - 600 and 800 mm.
- 4. Shelves.** Available in 1000 and 1250 mm width (depths see brackets above). Standard finish : light grey RAL 7035. (800 mm deep shelf = 2 x 400 mm)
- 5. Shelf stiffeners.** Are welded under the shelf in order to raise the load possibilities. 1, 2 of 3 per shelf.
- 6. Cross bracing.** 1 per 3 units. For racks higher than 2,25 m 2 cross braces are required.
- 7. Side & back panels.** Available in all standard heights, widths and depths. Available in wood or steel.


Accessories. For all other accessories from the Cornix Plus® range see below.

	5 shelves LOAD/ SHELF	DEPTH (mm)	WIDTH 1000 mm		EXTRA SHELF (BRACKETS INCLUDED)			
			STARTER UNIT CODE	€	EXTENSION UNIT CODE	€	CODE	€
HEIGHT 2000 mm	60 kg	300	TRT100302008D0		TRT100302008S0		T100308T0	
		350	TRT100352008D0		TRT100352008S0		T100358T0	
		400	TRT100402008D0		TRT100402008S0		T100408T0	
	100 kg	300	TRT100302001UD0		TRT100302001US0		T100301UT0	
		350	TRT100352001UD2		TRT100352001US2		T100351UT2	
		400	TRT100402001UD0		TRT100402001US0		T100401UT0	
		500	TRT100502001UD0		TRT100502001US0		T100501UT0	
		600	TRT100602001UD0		TRT100602001US0		T100601UT0	
	150 kg	800 (= 2 x 400)	TRT100802001UD2		TRT100802001US2		T100801UT2	
		300	TRT100302001UD0		TRT100302001US0		T100301UT0	
		350	TRT100352001UD2		TRT100352001US2		T100351UT2	
		400	TRT100402002UD2		TRT100402002US2		T100402UT2	
500		TRT100502002UD2		TRT100502002US2		T100502UT2		
600		TRT100602002UD2		TRT100602002US2		T100602UT2		
200 kg	800 (= 2 x 400)	TRT100802003UD2		TRT100802003US2		T100803UT2		
	300	TRT100302002UD2		TRT100302002US2		T100302UT2		
	350	TRT100352002UD2		TRT100352002US2		T100352UT2		
	400	TRT100402003UD2		TRT100402003US2		T100403UT2		
	500	TRT100502003UD2		TRT100502003US2		T100503UT2		
Cross brace	600	TRT100602003UD2		TRT100602003US2		T100603UT2		
	800 (= 2 x 400)	TRT100802003UD2		TRT100802003US2		T100803UT2		
	1000	TCR100G0	incl.	TCR100G0		-	-	

	5 shelves LOAD/ SHELF	DEPTH (mm)	WIDTH 1250 mm		EXTRA SHELF (BRACKETS INCLUDED)				
			STARTER UNIT CODE	€	EXTENSION UNIT CODE	€	CODE	€	
HEIGHT 2000 mm	120 kg	300	TRT125302001UD0		TRT125302001US0		T125301UT0		
		400	TRT125402002UD0		TRT125402002US0		T125402UT0		
		500	TRT125502002UD2		TRT125502002US2		T125502UT2		
		600	TRT125602002UD0		TRT125602002US0		T125602UT0		
	160 kg	800 (= 2 x 400)	TRT125802001UD2		TRT125802001US2		T125801UT2		
		300	TRT125302002UD2		TRT125302002US2		T125302UT2		
		400	TRT125402003UD2		TRT125402003US2		T125403UT2		
		500	TRT125502003UD2		TRT125502003US2		T125503UT2		
		600	TRT125602003UD2		TRT125602003US2		T125603UT2		
		800 (= 2 x 400)	TRT125802003UD2		TRT125802003US2		T125803UT2		
		Cross brace	1250	TCR125G0	incl.	TCR125G0		-	-



- 8. Plinth. For a neat finish of your rack.
- 9. CORBAC plastic bins.
- 10. MODULBOX plastic bins.
- 11. Garment hanging
- 12. Frame for suspended files
- 13. Special shelf with incorporated suspended file system.



- 14. Reinforcement beams. To obtain a higher load of the shelves (up to 400 kg) beams can be used as an extra support.
- 15. Stability beams. Replaces the cross bracing if your rack has to be 100% accessible from both sides.
- 16. Shelfender. At the front or backside of your shelf.
- 17. Steel dividers Cornix Plus®.

For the most up to date price : please consult us



You can install the divider exactly where you want.

STEEL DIVIDERS CORNIX PLUS®

DEPTH (mm)	300		350		400		500		600		800	
HEIGHT (mm)	CODE	€										
165	TSM3016G2		TSM3516G2		TSM4016G2		TSM5016G2		TSM6016G2		TSM8016G2	
215	TSM3021G2		TSM3521G2		TSM4021G2		TSM5021G2		TSM6021G2		TSM8021G2	
265	TSM3026G2		TSM3526G2		TSM4026G2		TSM5026G2		TSM6026G2		TSM8026G2	
315	TSM3031G2		TSM3531G2		TSM4031G2		TSM5031G2		TSM6031G2		TSM8031G2	
365	TSM3036G2		TSM3536G2		TSM4036G2		TSM5036G2		TSM6036G2		TSM8036G2	
415	TSM3041G2		TSM3541G2		TSM4041G2		TSM5041G2		TSM6041G2		TSM8041G2	
465	TSM3046G2		TSM3546G2		TSM4046G2		TSM5046G2		TSM6046G2		TSM8046G2	
515	TSM3051G2		TSM3551G2		TSM4051G2		TSM5051G2		TSM6051G2		TSM8051G2	
					TCLSMG0							

Clips for divider Cornix Plus®



◀ MODULAR COUNTERS

Based on the Cornix Plus® shelving system.

Well adapted for garages, whole-salers, industrial warehouses, etc.


Height 1040 mm. Standard lengths from 1052 mm up to 4058 mm. Longer counters are available on request (per module of 1000 or 1250 mm). Counter depth is always 500 mm with an overhanging worktop of 600 mm. Standard equipped with 3 shelves (2 levels) per module. Extra shelves are available at extra cost. An 800 mm deep counter (worktop 900 mm) is available on request.

Many accessories are available :

- plastic bins MODULBOX
- plinths for the backside of the counter
- 100% roll-out shelf (45 kg uniformly distributed load)
- steel dividers
- steel side panels
- rubber layer.

Technical characteristics :

- uprights blue RAL 5010
- shelves light grey RAL 7035
- side panels and frontpanels in white melamine
- worktop is a 39 mm scratchproof Formica panel rounded one side
- delivered unassembled. Installation on request.




LENGTH (mm)	MODULES	CODE	€
1052	1 x 1000	TCT601053	
1302	1 x 1250	TCT601303	
2054	2 x 1000	TCT602053	
2304	1 x 1000 + 1 x 1250	TCT602303	
2554	2 x 1250	TCT602553	
3056	3 x 1000	TCT603053	
3306	2 x 1000 + 1 x 1250	TCT603303	
3556	1 x 1000 + 2 x 1250	TCT603553	
3806	3 x 1250	TCT603803	
4058	4 x 1000	TCT604053	
Installation cost per full meter (indivisible)			TMONT3R

**There are of course 1000 and 1 other possibilities.
Can't you find the counter you are looking for in the above list
please contact us or ask for a visit of one of our project engineers.**



ACCESSORIES	DIM. (mm)	CODE	€
Plinth	900	TPL090G3	
Plinth	1000	TPL100G0	
Plinth	1250	TPL125G3	
Steel side panel (intermediate)	1000 x 430	TTC10050B3	
Extra shelf	900 x 500	T90501UT0	
100 kg uniformly distributed load; 2 brackets included.	1000 x 500	T100501UT0	
400 mm deep roll-out shelf	1250 x 500	T125502UT0	
45 kg uniformly distributed load; 2 brackets included.	850 x 500	T90508TE3	
	950 x 500	T100508TE3	
	1200 x 500	T125508TE3	
Dividers			see above
Plastic bins			see corbac (webshop)



◀ FOLD DOWN SHELF

The fold down shelf allows you to create the space required in order to consult quickly a file without narrowing permanently your aisle.

Only to be used as consulting shelf and not fitted for storage ! Is delivered with the necessary hinges and screws and can only be installed on a melamine side panel of 18 mm thick.

W x D (mm)	FOR CORNIX PLUS® SHELF WITH DEPTH (mm)	CODE	€
400 x 300	400	TPT40303	
600 x 300	600	TPT60303	



◀ RUBBER LAYER

Extremely suited for counters, workbenches, cupboards, etc. to avoid damage.

Two types are available : a solid rubber layer 3 mm thick and a corrugated rubber layer also 3 mm thick (on the thickest point).

DESCRIPTION	CODE	€
SOLID RUBBER 3 MM	JC3LR0	
• per full roll 10 m x 1,4 m	JC3LM0	
CORRUGATED RUBBER 3 MM	JC3SR0	
• per full roll 10 m x 1,2 m	JC3SM0	
• per meter 1 m x 1,2 m		

CUPBOARD DOORS ▶

In certain areas of your Cornix Plus® installation it can be necessary to insert a protected module. Thanks to the Cornix Plus® cupboard doors this can be done without problem. Cupboard doors are available in 1000 mm width and are 2000 mm high, including plinth and canopy.

Don't forget to order the necessary side & back panels !

Standard finish : doors light grey RAL 7035, steel side and back panels blue RAL 5010.

Each doorset is equipped as a standard with a day and night locking system with a sunk grip. The combination of dividers (see above) with the doors is no problem. The drawers below can also be combined with the cupboard doors. Glass shelves are available on request.



TYPE	H x W (mm)	CODE	€
Set cupboard doors	2000 x 1000	TPOR200100G0	

ADHESIVE PRICE RAILS ▶


To install identification labels in your Cornix Plus® shelving system. Available for the shelves of 1000 & 1250 mm. Heights 20, 34 of 42 mm. Transparent PVC.



You can find an extensive choice of magnetic labels & adhesive price rails in our webshop.


LENGTH (mm)	H (mm)	H LABEL (mm)	CODE	€
950	20	18	SDS20950T0	
1200	20	18	SDS201200T0	
950	34	30	SDS30950T0	
1200	34	30	SDS301200T0	
950	42	40	SDS40950T0	

HOW TO CALCULATE THE DIMENSIONS OF YOUR INSTALLATION ?



distance between uprights :
shelf 1000 mm : 960 mm (center/center upright : 1000 mm)
(useful length of shelf : 1000 mm)

depth :
depth shelf (e.g. 400 mm)
+ 2 x 15 mm (upright depth)



don't forget to add :

- ▶ 1x upright width (38 mm)
- ▶ the overhang of the base plate (only in case of steel base : 40 mm once to be added to the total length)

example :


3 bays of 1000 mm make a total of : $3 \times 1005 + 1 \times 38 = 3053 \text{ mm} + 40 \text{ mm overhang base plate} = 3093 \text{ mm}$

DRAWERS ►

For a further equipment of your Cornix Plus® installation steel drawers with a module width of 1000 mm are available. The built-in depth is 500 mm which means that the depth of your rack has to be 500 mm. The same drawer can also be installed in a 600 mm deep rack at an extra cost. However this does not change the dimensions of the drawer.

Each drawer runs on 2 heavy duty telescopic guides 100 % extensible and can carry up to 70 kg. A full length handle allows you to put a price rail onto it allowing you to mark the identification of the contents of the drawer (price rail is optional). A central locking system is also available as an option as are a full range of dividers and bins.

2 possible drawer heights : 100 & 200 mm. Finishing : light grey RAL 7035.



HOW TO DIVIDE YOUR DRAWER?

TYPE	USEFUL INT. DIM. W x D x H (mm)	TOTAL HEIGHT (mm)	CODE	€
T500/100	915 x 450 x 95	100	TTIR1005095G9	
T500/200	915 x 450 x 195	200	TTIR10050195G9	
Central locking system			TVCT9	
Extra cost built-in depth of 600 mm			TTS609	

1 Red conical polystyrene bins to be placed into the drawer

HEIGHT (mm)	W x D (mm)	CODE	€
65	75 x 75	6K7510005V	
65	75 x 150	6K7510105V	
65	150 x 150	6K7510205V	

2 Grooved dividers for primary division. Grey laquered steel dividers. Grooved (single sided for the sides, double sided for the ones in the middle) every 12,5 mm.

3 Dividers for secondary division. Aluminium dividers to be installed in the grooves of the primary dividers.

HEIGHT (mm)	70		130	
	LENGTH (mm)	CODE	€	CODE
Single sided 450	6K6145405V		6K6145505V	
	900	6K6145105V		6K6145205V
Double sided 450	6K6145705V		6K6145805V	

HEIGHT (mm)	60		120	
	LENGTH (mm)	CODE	€	CODE
50	6K6147005V		-	
100	6K6147205V		6K6148205V	
150	6K6147405V		6K6148405V	
300	6K6147805V		6K6148805V	
450	6K6147905V		6K6148905V	

ASK FOR A VISIT OF ONE OF OUR PROJECT ENGINEERS !



For certain applications galvanized shelves are required :
Cornix Plus® with sendzimir shelves, brackets, bracing and dividers.



**EUROPE'S FIRST MANUFACTURER
OF STORAGE SYSTEMS**

CORNIX PLUS® • MULTI-TIER & MEZZANINES

2 TIER INSTALLATION

3 TIER INSTALLATION



Multi-tier Cornix Plus® installation 2, 3 or 4 tier. For storage of small parts, archives, etc.



INCORPORATED STAIRCASES & HANDRAILS ARE ALSO AVAILABLE.

1 TIER + MEZZANINE




2 TIER + MEZZANINE




Multi-tier Cornix Plus® installation 2 or 3 tier with mezzanine on top. For storage of small parts, archives, ... and bulky goods on top.

CORNIX PLUS® • MOBILE STORAGE SYSTEM

*Bespoke
on request*
MEASUREMENTS



Mobile storage systems allow you to make a more efficient use of your available space in your office, your archive or in your warehouse. They are easy to handle, they reduce the intake of dust and on top of that the mobile bases can receive different types of shelving systems e.g. Cornix Plus® shelving system (1 & 2) or Minirack Plus® long span system (3).



WE CAN PROPOSE YOU TWO DIFFERENT SYSTEMS

THE FRICTION SYSTEM

in which the bases are pushed over a rail. This system is the cheapest but it is only suitable for short bases with a rather low load.

THE TRACTION SYSTEM

in which the bases are moved by a gearbox with gears that grip into a rail. Slipping becomes impossible and therefore lengths of 13 meter with heavier loads up to 35 tonnes can be achieved.

The best system in the market !

Your CORNIX engineer will make you a free quote for your mobile installation.

Delivered not assembled.
On request our specialized installers will install your mobile storage system. Ask for a free quote !



CORNIX® LIGHT • SHELVING SYSTEM



LIGHT SHELVING DERIVED FROM THE CORNIX PLUS® RANGE



BOLTLESS SHELVING SYSTEM CORNIX® LIGHT

The Cornix® Light shelving system is composed on one hand of uprights & brackets that clic into each other thus creating a solid frame and on the other hand the easily moved shelves. This type is a "light" version of the CORNIX PLUS® range and uses the same brackets, shelves and cross bracing. Accessories are not available. Assembling is as easy as the CORNIX PLUS® range.

This type of shelving system is recommended for light storage (maximum 100 kg per shelf - maximum 800 kg per bay) such as archives or small parts. Cheaper than the CORNIX PLUS® range.


- ▶ **Angle upright 40x25x1,50.** 4 uprights per starter unit, 2 per extension unit. Standard heights : 2 - 2,25 - 2,50 meter. Greater heights are not possible. Standard finish : sendzimir.
- ▶ **Plastic base.** Prevents damage by the upright to your floor or carpet.
- ▶ **Brackets.** Two per shelf. Depths : 300 - 400 - 500 and 600 mm. Sendzimir finish.
- ▶ **Shelves.** Available in 1000 mm standard width (depths see brackets above). Standard finish : sendzimir. (depth 500 mm = 2x250 / 600 = 2x300 mm)
- ▶ **Cross bracing.** 1 per 2 units. For racks higher than 2,25 m two cross braces are required. Standard finish : sendzimir.
- ▶ **Accessories :** not available in the Light range. Please consult the CORNIX PLUS® range.
- ▶ **Mezzanines & multi-tier installations :** not possible with this type of upright. For such installations please consult the CORNIX PLUS® range.

CORNIX® LIGHT rack width 1000 mm (height 2000, 2250 & 2500 mm) - finish completely sendzimir.

H (mm)	DEPTH (mm)	LOAD/ SHELF (kg)	NUMBER OF SHELVES	WIDTH 1000 mm		EXTRA SHELF (BRACKETS INCLUDED)			
				STARTER UNIT CODE	€	EXTENSION UNIT CODE	€	CODE	€
2000	300	100	5	TRC100302005DZ0		TRC100302005SZ0		T1003010ZT0	
	400	100	5	TRC100402005DZ0		TRC100402005SZ0		T1004010ZT0	
	500 (2x250)	100	5	TRC100502005DZ0		TRC100502005SZ0		T1005010ZT0	
	600 (2x300)	100	5	TRC100602005DZ0		TRC100602005SZ0		T1006010ZT0	
2250	300	100	6	TRC100302256DZ0		TRC100302256SZ0		T1003010ZT0	
	400	100	6	TRC100402256DZ0		TRC100402256SZ0		T1004010ZT0	
	500 (2x250)	100	6	TRC100502256DZ0		TRC100502256SZ0		T1005010ZT0	
	600 (2x300)	100	6	TRC100602256DZ0		TRC100602256SZ0		T1006010ZT0	
2500	300	100	6	TRC100302506DZ0		TRC100302506SZ0		T1003010ZT0	
	400	100	6	TRC100402506DZ0		TRC100402506SZ0		T1004010ZT0	
	500 (2x250)	100	6	TRC100502506DZ0		TRC100502506SZ0		T1005010ZT0	
	600 (2x300)	100	6	TRC100602506DZ0		TRC100602506SZ0		T1006010ZT0	
Extra cross bracing				TRC100Z0	incl.	TRC100Z0		-	-

Above you can find prices for starter units (4 light uprights, 5-6 shelves & 1-2 cross bracing) and for extension units (2 light uprights and 5-6 shelves, cross bracing to be added when required). Each rack is delivered not assembled and with the necessary plastic bases.

HOW TO CALCULATE THE DIMENSIONS OF YOUR INSTALLATION ?



example : 3 bays of 1000 mm make $3 \times 1010 + 1 \times 10 = 3040$ mm

total depth : depth shelf (e.g. 400 mm) + 5 mm

distance between uprights for shelves 1000 mm :

- starter unit : 950 mm (center/center upright : +/- 1005 mm)
- extension unit : 975 mm (center/center upright : +/- 1005 mm)
- intermediate unit : 1000 mm (center / center upright : +/- 1005 mm)
- the bracing can only be installed on a starter unit :

2 extension units have to be converted into 1 starter unit and 1 intermediate unit by inverting 2 uprights.

don't forget :

- ▶ add 1x 10 mm for the plastic base.



CORNIX® JUNIOR • BOLTED SYSTEM

ON STOCK



VARIATIONS WITH SHELVES & SLOTTED ANGLES

This product is the classic in the CORNIX range : it has been manufactured by us since 1958 in it's original design. Customers who bought this system 20, 30, 40 years ago can even today extend their installation with the same parts.


CORNIX® JUNIOR BOLTED SHELVING SYSTEM

- ▶ for garages, storage areas, workshops, factories, etc.
- ▶ multiple references : most ministries, schools, multinationals, boroughs and lots of small businesses.
- ▶ many references abroad : France, Gabon, Congo, ...
- ▶ alle steel parts are lacquered light grey RAL 7035.
- ▶ assembled with bolts and nuts.
- ▶ no bracing.
- ▶ in some cases bolts can be partly replaced by clips.

CORNIX® JUNIOR RACK width 1000 mm (height 2000 mm)

DEPTH (mm)	LOAD/ SHELF (kg)	NUMBER OF SHELVES	STARTER UNIT CODE	€	EXTENSION UNIT CODE	€	EXTRA SHELF CODE	€
300	60	5	TRJ100302008D0		TRJ100302008S0		T100308E0	
350	60	5	TRJ100352008D0		TRJ100352008S0		T100358E0	
400	90	5	TRJ100402001UD0		TRJ100402001US0		T100401UE0	
500	90	5	TRJ100502001UD0		TRJ100502001US0		T100501UE0	
600	90	5	TRJ100602001UD0		TRJ100602001US0		T100601UE0	


Above you can find the prices for starter units (4 junior slotted angles and 5 shelves) and extension units (2 junior slotted angles and 5 shelves) based on junior slotted angles. Each rack is delivered not assembled with the necessary plastic bases and bolts & nuts. Lacquered light grey. The indicated loads are valid only for starter units. Extension units may take an inferior load.



Delivered not assembled. Installation on request. Ask for a free quote !

DESCRIPTION	DIMENSIONS (mm)	CODE	€/ pc
SLOTTED ANGLES (assembled with M6 bolts)			
junior • gauge 1,50 mm • length 2 m	grey 54 x 31 x 1,50 x 2000	T5431152MG0	
junior • gauge 1,50 mm • length 3 m	grey 54 x 31 x 1,50 x 3000	T5431153MG0	
junior • gauge 1,50 mm • length 2 m sendzimir	54 x 31 x 1,50 x 2000	T5431153MZ0	
junior • gauge 1,50 mm • length 3 m sendzimir	54 x 31 x 1,50 x 3000	T5431153MZ0	
SHELVES			
<i>Regular type • 60 kg</i>			
10003008 • steel gauge 8/10	1000 x 300 x 0,8	T100308G0	
10003508 • steel gauge 8/10	1000 x 350 x 0,8	T100358G0	
<i>Modèle renforcé • 90 kg</i>			
10004001U • steel gauge 8/10	1000 x 400 x 0,8 + 1U	T100401UG0	
10005001U • steel gauge 8/10	1000 x 500 x 0,8 + 1U	T100501UG0	
10006001U • steel gauge 8/10	1000 x 600 x 0,8 + 1U	T100601UG0	
<i>Other dimensions on request</i>			
ACCESSORIES			
bolts M6x10 • (packed per 50 pcs)	∅ 6 x 10	JBE6X10Z	
plastic base to prevent damage to floor	54 x 31	JPP5431N0	
shelf support clip	25 x 23	TTQZ9	
GSJ • corner plate junior	70 x 95	TGSJG0	


HOW TO CALCULATE THE DIMENSIONS OF YOUR INSTALLATION ?



- total depth : depth shelf (e.g. 400 mm) + 5 mm
 distance between uprights for shelves 1000 mm :
- starter unit : 938 mm (center/center upright : +/- 1005 mm)
 - extension unit : 969 mm (center/center upright : +/- 1005 mm)

don't forget :

- ▶ add 1x 10 mm for the plastic base.





YOUR CHOICE OF COLOURS

Standard colour for this product (on stock) :

Gentian blue	uprights	ral 5010	
Light grey	shelves	ral 7035	

(bracing & small items : sendzimir)

Other standard colours without surcharge
(lead time +/- 4 weeks) :

Ivory (cream)		ral 1013	
Zinc yellow		ral 1018	
Orange-red		ral 2002	
Light grey		ral 7035	



(bracing & small items always sendzimir)

Other ral colours at extra cost (lead time +/- 6 weeks)

(bracing & small items always sendzimir).

Sendzimir shelves also available (+/- 4 weeks).

OTHER CORNIX® PRODUCTS



STORAGE SYSTEMS FOR LIFE

www.cornix.eu

CORNIX FLANDERS

ANTWERPEN (Kiel)

Boomsesteenweg, 492
B-2020 Antwerpen

☎ ++/32/(0)3/240 11 30

☎ ++/32/(0)3/825 30 90

✉ sales@cornix.eu

CORNIX NETHERLANDS

DOETINCHEM (pas de showroom)

Kruidenlaan 7
NL-7006 TD Doetinchem

☎ ++/32/(0)3/240 11 30

☎ ++/32/(0)3/825 30 90

✉ sales.nl@cornix.eu

CORNIX WALLONIA

NIVELLES

Rue de la Recherche 6A, Z.I. 1 Nivelles Sud
B-1400 Nivelles

☎ ++/32/(0)67/411 241

☎ ++/32/(0)67/411 249

✉ sales@cornix.be

CORNIX EXPORT SALES

NIVELLES

Rue de la Recherche 6A, Z.I. 1 Nivelles Sud
B-1400 Nivelles

☎ ++/32/(0)67/894 225

☎ ++/32/(0)67/894 220

✉ export@cornix.eu